



Taśma GERLED® Professional IP20 SMD 5050 24V

GERLED® Professional LED strip
IP20 SMD 5050 24V

GERLED® Professional striscia LED
IP20 SMD 5050 24V

GERLED® Professional LED-Streifen
IP20 SMD 5050 24V



Podwójna warstwa PCB

Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



Stopień ochrony IP20

Protection class
Grado di protezione (IP)
IP-Klassee



3 lata gwarancji

3 years warranty
3 anni di garanzia
3 Jahre Garantie



Współczynnik oddawania barw

Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex




Zgodność z CE

CE Compliance
Conformità CE
CE-Zertifikat



Zywość

Life span
Vitalità
Lebensdauer



Kąt świecenia

Viewing angle
Anglo luminoso
Beleuchtungswinkel



Temperatura pracy

Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



Temperatura magazynowania

Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS

RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS24GW01550RGBXX	RGB	R:633 G:517 B:450	30 LED/m	7,2 W/m	310-315 lm/m
05TS24GW03050RGBXX			60 LED/m	14,4 W/m	
05TS24EW01550RGC08	RGB + BIAŁY CIEPŁY RGB + WARM WHITE RGB + BIANCO CALDO RGB + WARMWEISS	2900K-3100K R:633 G:517 B:450	30 LED/m	7,2 W/m	310-315 lm/m
05TS24EW03050RGC08			60 LED/m	14,4 W/m	
05TS24EW01550RGZ08	RGB + BIAŁY ZIMNY RGB + COOL WHITE RGB + BIANCO FREDDO RGB + KALTWEISS	6000K-6500K R:633 G:517 B:450	30 LED/m	7,2 W/m	310-315 lm/m
05TS24EW03050RGZ08			60 LED/m	14,4 W/m	

30 LED/m



sekcja cięcia co 165 mm (5 diod)
cutsection every 165 mm (5 diodes)
sezione di taglio ogni 165 mm (5 diodi)
Schnittabschnitt alle 165 mm (5 LEDs)



60 LED/m



sekcja cięcia co 100 mm (6 diod)
cutsection every 100 mm (6 diodes)
sezione di taglio ogni 100 mm (6 diodi)
Schnittabschnitt alle 100 mm (6 LEDs)

